

	MODEL 9220	MODEL 9430		5200 DRAPER / 9125 AUGER	
ENGINE			DRAPER HEADER		
Model	Cummins (Turbocharged) B3.3T	SisuDiesel (Turbocharged & Intercooled) 4.4 CTA	Center delivery version: ft. (m)	18, 22, 25, 30, 36 (5.5, 6.7, 7.6, 9.1)	
HP	85	120	Double Swath version: ft. (m)	22, 25, 30 (6.7, 7.6, 9.1)	
Drive System Type	Hydrostatic with planetary final reduction	Hydrostatic with planetary final reduction	Flotation	Hydraulic	
Speed Range: mph (kph)	0-11 (0-17.7)	0-15 (0-24)	Knife type	Over-serrated sections and forged guards	
Transmission	Single Speed	Dual Speed	Knife drive	Hydraulic motor and SCH gearbox, 1300 strokes/min.	
CAPACITIES			Reel drive	Hydrostatic motors, speed control from cab, 0-60 rpm	
Fuel Tank: gal. (L)	80 (227)	80 (227)	Draper type	41 in (1,040 mm) rubberized	
TIRES			Draper drive	Hydrostatic motors, speed control from cab, 0-600 ft/min.	
Front: turf	18.4 x 26 turf tread	18.4 x 26 turf tread	Swath opening: in. (mm)	54-70 (1,370-1,780)	
Front: bar tread	16.9 x 28 R4 bar tread & 18.4 x 26 RI bar tread	16.9 x 28 R4 bar tread & 18.4 x 26 RI bar tread	AUGER HEADER		
Rear caster: implement rib - Adj. Axle - Fixed Axle	14.1 x 16.1 12.5L - 15	14.1 x 16.1 12.5L - 15	Cutting width: ft. (m)	14, 16 or 18 (4.3, 4.9 or 5.5)	
DIMENSIONS			Reel	5-bat with camtrak steel flex tines	
Length with header in. (mm)	257.6 (6,543)	257.6 (6,543)	Cutterbar	Dual sickles, 1,840 strokes/min., hydraulic swaybar drive	
Wheelbase: in. (mm)	140 (3,556)	140 (3,556)	Knife stroke: in. (mm)	3 (76)	
Width with 18.4 tires: in. (mm)	146.5 (3,722)	146.5 (3,722)	Upper auger: in. (mm)	9 (229)	
Front tread width: in. (mm)	127.6 (3,241)	127.6 (3,241)	Lower auger: in. (mm)	10 (254)	
Rear tread width: in. (mm) - Adj. Axle - Fixed Axle	84.4 - 120 (2,144 - 3,048) 120 (3,048)	84.4 - 120 (2,144 - 3,048) 120 (3,048)	Conditioner: in. (mm)	110 (2,794)	
Underframe clearance: in. (mm)	39.8 (1,010)	39.8 (1,010)	Engaging Steel-Steel or Rubber-Steel		
Height to top of cab: in. (mm)	130.9 (3,324)	130.9 (3,324)	OPTIONAL TRACTOR EQUIPMENT		
Weight without header: lbs. (kgs)	8,100 (3,674)	8,300 (3,765)	Windshield wiper kit		
CAB			AM/FM Radio and CD, with weatherband		
Comfort	Quiet cab, A/C and heater, air ride seat and tilt steering wheel, tinted glass	Quiet cab, A/C and heater, air ride seat and tilt steering wheel, tinted glass	Tractor performance monitor		
CONTROLS			Rotary screen (Model 9220)		
	Ground speed, throttle, header engagement, parking brake, full instrumentation	Ground speed, throttle, header engagement, parking brake, full instrumentation	Easy attach header angle kit		
LIGHTS			Quick couplers		
	5 front halogen, 2 rear cab halogen, 2 rear tractor halogen, 4 amber flashers	5 front halogen, 2 rear cab halogen, 2 rear tractor halogen, 4 amber flashers	Hydraulic guard angle (Model 9220)		
			Header Height Indicator		